

What is claimed is:

1. A process for treating dicarboxylic acids, said process comprising:
 - (a) heating said dicarboxylic acid to a temperature above its melting point;
 - (b) adding water to said dicarboxylic acid.
2. A process according to Claim 1 wherein the dicarboxylic acid is selected from C₂-C₁₃ dicarboxylic acids and mixtures thereof.
3. A process according to Claim 1 wherein the water is added within 10 minutes of the dicarboxylic acid becoming molten.
4. A process according to Claim 1 wherein water is added in an amount of at least 1g per 1,000g of dicarboxylic acid.
5. A process according to Claim 1 wherein at least 1g of water per 1,000g of dicarboxylic acid is added per minute.
6. A process according to Claim 1 wherein the dicarboxylic acid is heated to a temperature at least 5°C above its melting point.
7. A process according to Claim 2 wherein the dicarboxylic acid is hexanedioic acid.
8. A composition comprising molten dicarboxylic acid and water characterized in that said composition comprises at least 1g of water per 1,000g of dicarboxylic acid.
9. A composition according to Claim 9 wherein the dicarboxylic acid is selected from C₂-C₁₃ dicarboxylic acids and mixtures thereof.
10. A composition according to Claim 8, wherein the composition additionally comprises a chelant.
11. A process for coating detergent tablets with a dicarboxylic acid, wherein said dicarboxylic acid is retarded from discoloring, said process comprising:
 - (a) heating a dicarboxylic acid to a temperature above its melting point;
 - (b) adding water to said dicarboxylic acid; and
 - (c) applying the dicarboxylic acid to the tablet.